

Class Rules

Modified Gas 4x4 Trucks 6500 lbs

Hitch Point is to be rear most point of vehicle with a maximum height of 26 inches.

Tires must be DOT approved for highway use with a maximum diameter of 35 inches.

All Vehicles must be equipped with driveshaft hoops with minimum thickness of 1/4" thick steel over each visible u-joint.

All Vehicles must retain factory production pick up truck body and chassis.

Engines used must have been available from factory in a pick up truck.

Any added weight must be secured and must not exceed 60 " past centerline of front axle.

Track official and event coordinators reserve the right to refuse any vehicle from participating if deemed unsafe or unfit.

Modified Diesel 8500 lbs

Hitch Point is to be rear most point of vehicle with a maximum height of 26 inches.

Tires must be DOT approved for highway use with a maximum diameter of 35 inches.

All Vehicles must be equipped with driveshaft hoops with minimum thickness of 1/4" thick steel over each visible u-joint.

All Vehicles must have been available as factory production 3/4 or 1 ton diesel pick up truck.

Engines used must have been available from factory in a 3/4 or 1 ton diesel pick up truck.

Any added weight must be secured and must not exceed 60 " past centerline of front axle.

Track official and event coordinators reserve the right to refuse any vehicle from participating if deemed unsafe or unfit.

Stock Gas 6500 lbs

Vehicles must be considered fit, legal, licensed and insured for the road. Must have proof of insurance upon request from event coordinator and/or track official.

Hitch point is to be rear most point of the vehicle with a maximum height of 22 inches. Reese style hitches only.

Blocking of rear suspension to reduce or eliminate travel is not permitted.

Any added weight must be secured in the bed of the truck. No weights or ballast permitted in the cab. No exceptions.

Engines must be the factory block and heads for the make model and year of the vehicle and be of stock appearance.

Engines must retain factory intake manifold and exhaust manifolds.

Engines must be naturally aspirated unless otherwise factory equipped with turbo/superchargers.

Engines must be fueled by pump gas only. No secondary fuels; this includes but is not limited to alcohol, propane, water, nitrous oxide, and oxygen.

Exhaust must exit rearward of the cab.

All Vehicles must be equipped with driveshaft hoops with minimum thickness of 1/4" thick steel over each visible u-joint if:

tires exceed 33" in diameter

suspension has been modified in ANY way

Stock Diesel 8500 lbs

Vehicles must be considered fit, legal, licensed and insured for the road. Must have proof of insurance upon request from event coordinator and/or track official.

Hitch point is to be rear most point of the vehicle with a maximum height of 22 inches. Reese style hitches only.

Blocking of rear suspension to reduce or eliminate travel is not permitted.

Any added weight must be secured in the bed of the truck. No weights or ballast permitted in the cab. No exceptions.

Engines must be the factory block and heads for the make model and year of the vehicle and be of stock appearance.

Engines must retain factory intake manifold, exhaust manifold(s) and turbocharger.

Diesel fuel only. No secondary fuels. This includes but is not limited to; alcohol, propane, water, nitrous oxide, and oxygen.

Exhaust must exit rearward of the cab.

All Vehicles must be equipped with driveshaft hoops with minimum thickness of 1/4" thick steel over each visible u-joint if:

tires exceed 33" in diameter

suspension has been modified in ANY way

Local Tractors

The tractor/ truck pull coordinators have the right to determine the area boundaries that a puller can be considered to be a local puller by setting a distance the puller must live within from the pull grounds or by county or region.

Each tractor may pull in a maximum of two classes at one event.

Tractors must have a hood, floorboards, grills(s), and fenders and must be stock appearing for that model

Engines must be stock or manufacturers replacement for the model with no visible engine modifications.

Maximum RPM's is 10% over manufacturer's high idle.

Tractors exhaust systems with mufflers must be pointed away from the crowd.

Dry ice or water injection may not be used. Unless approved by tractor/truck pull committee.

No weights behind the rear axle. Weights must be securely mounted and must not move during the pull. Any lost ballast will result in disqualification.

All classes 7500 lbs and under will have a drawbar maximum height of 18"

All classes over 7500 lbs will have a maximum height of 20".

The minimum draw bar length is 18" from the center of the rear wheels to the point of hook.